

Surface Mount Multilayer Varistors

High Surge Protection (HA) Series

Features:

- Fast Response < 0.5 ns
- Low Capacitance
- Low Clamping Voltage and High Energy Absorption

Application Fields:

- Telecommunications
- Automotive Systems
- Data Systems
- Power Supplies

Ordering Information:

Part Number	Working Voltage (max)		Breakdown Voltage 1 mA (V)	Peak Current (max) 8/20 μ s (A)	Clamping Voltage (max)		Energy Absorption (max) 10/1000 μ s (J)	Typical Capacitance 1 KHz (pF)
	AC (V _{RMS})	DC (V)			(A)	(V)		
MLV1206HA014V0200	11	14	18 (15.3~20.7)	200	1	30	0.5	1200
MLV1206HA018V0200	14	18	24 (21.6~27.0)	200	1	39	0.5	780
MLV1206HA022V0200	17	22	27 (24.3~29.8)	200	1	44	0.7	750
MLV1206HA026V0200	20	26	33 (29.7~36.3)	200	1	54	1.0	700
MLV1206HA030V0200	25	30	39 (35.1~42.9)	200	1	65	1.0	510
MLV1206HA038V0200	30	38	47 (42.3~51.7)	200	1	77	1.1	440
MLV1210HA014V0400	11	14	18 (15.3~20.7)	400	2.5	30	1.2	2000
MLV1210HA018V0400	14	18	24 (21.6~27.0)	400	2.5	39	1.4	1600
MLV1210HA022V0400	17	22	27 (24.3~29.8)	400	2.5	44	1.7	1500
MLV1210HA026V0400	20	26	33 (29.7~36.3)	400	2.5	54	1.9	880
MLV1210HA030V0400	25	30	39 (35.1~42.9)	400	2.5	65	1.7	800
MLV1210HA038V0400	30	38	47 (42.3~51.7)	400	2.5	77	2.0	530
MLV1812HA018V0800	14	18	24 (21.6~27.0)	800	5	38	2.3	3500
MLV1812HA030V0800	25	30	39 (35.1~42.9)	800	5	65	3.7	2350
MLV1812HA038V0800	30	38	47 (42.3~51.7)	800	5	77	4.2	1600
MLV1812HA045V0800	35	45	56 (50.4~61.6)	800	5	90	4.2	1200
MLV2220HA014V1200	11	14	18 (15.3~20.7)	1200	10	30	5.4	10500
MLV2220HA018V1200	14	18	24 (21.6~27.0)	1200	10	39	5.8	8500
MLV2220HA022V1200	17	22	27 (24.3~29.8)	1200	10	44	7.2	8300
MLV2220HA030V1200	25	30	39 (35.1~42.9)	1200	10	65	9.6	6000
MLV2220HA038V1200	30	38	47 (42.3~51.7)	1200	10	77	12.0	4000
MLV2220HA045V1200	35	45	56 (50.4~61.6)	1200	10	90	12.0	3500

Surface Mount Multilayer Varistors

Product Identification:

MLV 0402 ES 012V 0100 N T
(1) (2) (3) (4) (5) (6) (7)

(1) Series Code:

MLV – Surface Mount Multilayer Varistor

MVA -- MLV Array

(2) Size Code:

Standard EIA Chip Size

(3) Application Code:

ES – Electro-static Discharge Protection

NA – Normal Surge Protection

HA – High Surge Protection

(4) Max. Working Voltage:

012V – 12 V

(5) Capacitance for ES Series:

0100 – 100 pF

02R5 – 2.5 pF

Peak Current for HA/NA Series: **0100** – 100 A

(6) Capacitance Tolerance for ES Series:

N – ± 30%

P – **Special**

(7) Packaging Code:

T – Tape & Reel

Operating Temperatures:


-55°C to +85°C for size 0603 or smaller

-55°C to +125°C for size 0805 or larger

Surface Mount Multilayer Varistors


Shape and Dimensions:

MLV Series



Size	L (mm)	W (mm)	T (mm)	E (mm)
0201	0.60 ± 0.03	0.30 ± 0.03	0.30 ± 0.03	0.30 ± 0.03
0402	1.00 ± 0.10	0.50 ± 0.10	0.50 ± 0.10	0.25 ± 0.10
0603	1.60 ± 0.15	0.80 ± 0.15	0.90 max.	0.30 ± 0.10
0805	2.00 ± 0.20	1.25 ± 0.15	1.00 max.	0.30 ± 0.10
1206	3.20 ± 0.20	1.60 ± 0.15	1.20 max.	0.50 ± 0.20
1210	3.20 ± 0.20	2.50 ± 0.20	1.50 max.	0.50 ± 0.20
1812	4.50 ± 0.20	3.20 ± 0.20	2.00 max.	0.60 ± 0.20
2220	5.70 ± 0.20	5.00 ± 0.20	3.00 max.	0.60 ± 0.20

ESD Array



Size	0508	0612
L (mm)	2.00 ± 0.20	3.20 ± 0.20
W (mm)	1.25 ± 0.20	1.60 ± 0.15
T (mm)	0.80 max.	0.95 max.
A (mm)	0.20 ± 0.10	0.20 ± 0.10
B (mm)	0.25 ± 0.05	0.40 ± 0.15


Terms and Definitions:

Term	Definition
Max. Working Voltage	Maximum steady-state DC operating voltage with typical leakage current less than 50 μ A at 25°C
Varistor Voltage (BDV)	Breakdown DC voltage measured at current of 1 mA
Max. Clamping Voltage	Maximum peak voltage across the part, measured at a specified pulse current and waveform
Surge Current	Maximum peak current with the specified 8/20 μ s waveform without damage
Surge Shift $\Delta V/V$	The change of varistor voltage after applying the specified surge current
Energy Absorption	Maximum energy dissipated with a specified 10/1000 μ s waveform without damage
Typical Capacitance	Capacitance measured with voltage bias less than 0.5 V_{RMS} at 1 KHz or 1 MHz
Nonlinear Exponent α	$\alpha = (\log(V_{1mA}/V_{0.1mA}) / \log(I_{V1mA}/I_{V0.1mA}))$
Leakage Current	Typical leakage current at 25 °C < 50 μ A; Maximum leakage 200 μ A.
Cut-off Frequency	The frequency of -3 dB insertion loss

Surface Mount Multilayer Varistors


Recommended Land Patterns:

MLV Series



Size	Solder pad layout		
	A (mm)	C (mm)	D (mm)
0201	0.25~0.35	0.20~0.30	0.25~0.35
0402	0.4~0.6	0.5~0.6	0.5~0.7
0603	0.9~1.2	0.6~1.0	0.8~1.2
0805	1.0~1.5	1.2~1.5	1.0~1.4
1206	1.8~2.5	1.2~1.8	1.0~1.4
1210	1.8~2.5	2.2~3.0	1.0~1.4
1812	2.5~3.3	2.8~3.6	1.2~1.8
2220	3.8~4.6	4.8~5.5	1.2~1.8

ESD Array Series



Size	A (mm)	B (mm)	D (mm)	F (mm)	G (mm)
0508	2.10	0.40	2.50	0.50	0.35
0612	2.60	0.80	3.60	0.80	0.50

Surface Mount Multilayer Varistors


Environmental Tests:

No.	Test	Requirement	Test condition	Test reference
1	Soldering heat resistance	BDV change $\leq \pm 10\%$ No mechanical damage	One dip at 260°C for 5 sec.	MIL-STD-202 Method 210 IEC 60068-2-20
2	Solderability	New solder coverage $\geq 80\%$	One dip at 255°C for 5 sec. Non-active flux	MIL-STD-202 Method 208 IEC 60068-2-20
3	Maximum surge current	BDV change $\leq \pm 10\%$ No mechanical damage	100 pulses of 8/20 μs with maximum surge current and 30 sec. interval at 25°C and 30 ~ 65% RH	CECC 42000 IEC 1051-1 Test 4.5
4	Maximum surge energy	BDV change $\leq \pm 10\%$ No mechanical damage	100 pulses of 10/1000 μs with maximum surge current and 90 sec. interval at 25°C and 30 ~ 65% RH	CECC 42000
5	Thermal cycling	BDV change $\leq \pm 10\%$ No mechanical damage Leakage current $\leq 200 \mu\text{A}$	5 cycles between -40°C and 125°C with 30 min. dwell time at the temperature extremes and 60 min. dwell time at 25°C	CECC 42000 IEC 60068-2-14
6	Low temperature resistance	BDV change $\leq \pm 10\%$ No mechanical damage Leakage current $\leq 200 \mu\text{A}$	1000 hr at -50°C	IEC 60068-2-1
7	Low temperature load resistance	BDV change $\leq \pm 10\%$ No mechanical damage Leakage current $\leq 200 \mu\text{A}$	1000 hr at -50°C with working voltage applied	IEC 60068-2-1
8	High temperature resistance	BDV change $\leq \pm 10\%$ No mechanical damage Leakage current $\leq 200 \mu\text{A}$	1000 hr at 150°C	MIL-STD-202 Method 108 CECC 42000
9	High temperature load resistance	BDV change $\leq \pm 10\%$ No mechanical damage Leakage current $\leq 200 \mu\text{A}$	1000 hr at 85°C with working voltage applied	CECC 42000
10	Humidity resistance	BDV change $\leq \pm 10\%$ No mechanical damage Leakage current $\leq 200 \mu\text{A}$	500 hr at 40°C and 90 ~ 95% RH	MIL-STD-202 Method 103 IEC 60068-2-3 CECC 42000;
11	Humidity load resistance	BDV change $\leq \pm 10\%$ No mechanical damage Leakage current $\leq 200 \mu\text{A}$	500 hr at 40°C and 90 ~ 95% RH with working voltage applied	MIL-STD-202 Method 103 IEC 60068-2-3 CECC 42000
12	ESD contact test*	Varistor voltage change > 115% working voltage	Contact electrostatic discharge 100 times with 1 second intervals at 8 KV (Level 4) and polarity: +,-	IEC 61000-4-2
13	ESD air test*	Varistor voltage change > 115% working voltage	Air contact electrostatic discharge 100 times with 1 second intervals at 15 KV (Level 4) and polarity: +,-	IEC 61000-4-2

* For ES series only.

Surface Mount Multilayer Varistors

Soldering Temperature Profile:



Profile Feature	Pb-Free Assembly
Preheat/Soak Temperature Min (T_{smin}) Temperature Max (T_{smax}) Time (t_s) from (T_{smin} to T_{smax})	150°C 200°C 60~120 seconds
Ramp-up rate (T_L to T_p)	3°C/second max.
Liquidous temperature (T_L) Time (t_L) maintained above T_L	217°C 60~150 seconds
Peak package body temperature (T_p)	260°C
Time (t_p)* within 5°C of the specified classification temperature (T_c)	30 seconds *
Ramp-down rate (T_p to T_L)	6°C/second max.
Time 25°C to peak temperature	8 minutes max.
* Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum	

Disclaimer

Specifications are subject to change without notice. AEM products are designed for specific applications and should not be used for any purpose (including, without limitation, automotive, aerospace, medical, life-saving applications, or any other application which requires especially high reliability for the prevention of such defect as may directly cause damage to the third party's life, body or property) not expressly set forth in applicable AEM product documentation. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Warranties granted by AEM shall be deemed void for products used for any purpose not expressly set forth in applicable AEM product documentation. AEM shall not be liable for any claims or damages arising out of products used in applications not expressly intended by AEM as set forth in applicable AEM product documentation. The sale and use of AEM products is subject to AEM terms and conditions of sale. Please refer